

HIGH VOLTAGE SWITCHGEAR

HIGH PERFORMANCE HIGH VOLTAGE
METAL-CLAD SWITCHGEAR



**Powering the Future
with Precision and Control**

EDMP's metal-clad switchgear is a high-performance indoor solution for three-phase AC 50Hz power systems up to 40.5kV. Designed for substations in power plants, industrial sites, rail transit systems, and high-rise buildings, it supports single bus and sectionalized configurations, ensuring reliable power reception, distribution, and system protection with integrated control and monitoring functions.

Compatible with ABB's VD4 series and ZN40.5-85 indoor vacuum circuit breakers, EDMP's switchgear offers compact design, easy maintenance, and exceptional mechanical and electrical performance. Built for flexibility and long-term reliability, it is a trusted solution for demanding medium-voltage applications.



ENERGY STORAGE

**HIGH PERFORMANCE HIGH VOLTAGE
METAL-CLAD SWITCHGEAR**

■ Features & Functions

Rated Voltage		40.5kV
Rated Current		630A, 1250A, 1600A, 2000A, 3150A
Rated Frequency		50Hz
Rated Insultation Level	1-Munite Power Frequency Withstand Voltage	50Hz
	Lightning Impulse Withstand Voltage	118kV
	1-Munite Power Frequency Withstand Voltage (Circuit Breaker)	185kV
	Lightning Impulse Withstand Voltage (Circuit Breaker)	215kV
Rated Short-Cicuit Breaking Current		25kA / 31.5kA / 40kA
Rated Short-Time Withstand Current		25kA / 31.5kA / 40kA
Rated Peak Withstand Current		50kA / 63kA / 80kA
Rated Short-Circuit Making Current		50kA / 63kA / 80kA
Duration of Rated Short-Time Withstand Current		4s
Rated Operating Sequence		O-0.3s-CO-180s-CO
Degree of Protection		IP4X
External Dimensions (Depth x Width x Height)		1400/1680 × 2800/3200 × 2600
Weight		1000kg
High Voltage Switchgear		Copyright

■ Operating Conditions

Item	Specification
Ambient Temperature	-10°C ~ +45°C
Max Daily Temperature Variation	Monthly average relative humidity: ≤%90;Daily average relative humidity: ≤%95
Seismic Intensity	≤ Level 8
Pollution Level	Level III
Control and Operating Voltage	DC Power Supply: DC 220V AC Power Supply: AC 220V ±%10 (60/50Hz) (Total harmonic distortion ≤ %5)

EDMP GROUP
📍 33 Burwood Park Road,
Walton-on-Thames, KT12 5LH,
United Kingdom

EDMP JAFZA
📍 PO Box 125428, Plot No. MO0147C, Junction of N400 & N406
Streets Jebel Ali Free Zone, Dubai, United Arab Emirates
✉ info@edmpgroup.com 🌐 www.edmpgroup.com